

## **Product information Formversiegler**

Description Low-volatility, water-miscible solvent for spraying on green sand moulds.

Field of use Moulding

> Formversiegler is used as surface hardener for natural and synthetic green sand moulds in light and heavy metal casting.

Formversiegler leads to the following improvements:

- Reduction of sand elutions - Prevention of sand scabs

- Higher dimensional accuracy of sand mould

- Higher casting surface quality

**Application** Formversiegler is to use undiluted in supply condition.

> The release agent should be sprayed thinly and evenly on the clean pattern surface. The coat is applied by conventional spray equipment by hand or automatically by spray units. A drying or flame treatment of the moulding

surface is not necessary.

To further improve the casting surface, the product can be mixed with graphite

powder in a ratio of 5:1.

**Technical Data** Density (20 °C): approx. 1,12 g/cm3

> Viscosity (20 °C): approx. 35 mPas Boiling point/boiling range: approx. 240-250 °C

Flash point: > 135 °C

**Packaging** Can á 30 kg and disposable drum á 230 kg

Store Formversiegler tightly closed in a dry, well-ventilated place; protect Storage

from heat and direct sunlight.

Shelf life 6 months when properly stored inside in original unopened container.

Close container tightly after usage. Prevent introduction of air / oxygen. Do not store in galvanized containers.

Regulations and information

Formversiegler is classified and labeled according to the CLP regulation

and corresponds to the current EC regulation.

Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety

data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required. HN/MT status 06/15

Technofond Gießereihilfsmittel GmbH • Am Pfaffensee 17 • 67376 Harthausen Phone: +49-6344-969780 ● Fax: +49-6344-9697855 ● www.technofond.com ● info@technofond.com